MAILLIS STRAPPING SYSTEMS - USA

M. J. MAILLIS GROUP

POWER HP 25

BATTERY STRAPPING TOOL WITH FRICTION WELD SEAL FOR (PET) DIGITAL CONTROL — FLAT AND ROUND SURFACES

TECHNICAL DATA / APPLICATIONS:

Compact, versatile and easy to use battery powered strapping tool equipped with <u>equiped with two Li</u>
<u>-ion Batteries and one Charger</u>. This tool is suitable for heavy duty industrial applications.
Tool set for **1.0**"(**25mm**) PET strap.

Package type	Flat 5" minimum diameter (120mm)
	Round 28" minimum diameter (700mm)
Strap type	PET
Strap Width	1" (25mm)
Strap thickness	From .038"051" (1.0mm up to 1.3mm)
Max. Tension	Around 990 lbf. (4500N)
Max. Tension speed	Around 39.5' min. (12 mt/min)
Joint type	Friction Weld Seal
Weight	Around 9 lbs (4.15 Kg) (battery included)
Order Code: POWER HP 25	154.990.810

HD TENSIONING MOTOR

- **DEWALT MOTOR**
- * REPLACEABLE BRUSHES
- * HIGH EFFICIENCY
- *** HIGH POWER**
- *** MAXIMUM PERFORMANCE**
- *** LONGER LIFE**
- *** BATTERY Li-ion SP1**

CELLS MFG. BY SAMSUNG





CHARGER FOR Li-ion BATTERY



MAILLIS STRAPPING SYSTEMS—USA Inc. 404 Wall Street, Fountain Inn, SC 29644

Phone: 877-962-4648 / Fax: 864-409-0367 / Web: maillisstrapping.com / E-mail: info@maillisstrapping.com